

## SAFETY DATA SHEET

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY.

Product Name: GRAFIMOVE  
Intended use: Vinyl Glue Remover

Manufacturer: GRAFITYP UK LIMITED  
Address: Grafitack House  
103 Mariner  
Tamworth  
Staffordshire  
B79 7UL

Telephone: 01827 300500  
Telefax: 01827 51333

### 2. COMPOSITION/INFORMATION ON INGREDIENTS.

INGREDIENT NAME	CAS No.	Symbol	RISK (R No.)	CONTENTS
Propan-2-ol	67-63-0	None	None	>50

### 3. HAZARDS IDENTIFICATION.

Eye Contact: Irritating to eyes.

Skin Contact: Slight skin irritant. Prolonged or repeated contact may cause dermatitis.

Inhalation: High Levels of vapour/mist may cause dizziness. Can cause irritation of the respiratory tract.

Ingestion: Single dose oral toxicity is low. Aspiration may cause rapid absorption via Lungs, resulting in injury to other body systems.



Tel: 01827 300500  
Fax: 01827 51333  
Email sales@grafityp.co.uk  
Website: www.grafityp.co.uk

Directors:  
L.J. Gilbert (Managing Director) H. Bosman Jr. (Secretary) R. Coolen (Director)  
J. Bartnicki (Technical Director) N. Stevenson (Sales Director)  
Grafityp UK Limited. Registered Office: Grafitack House, 103 Mariner, Tamworth, Staffordshire, B79 7UL.  
Registration Number: 2191134 England.



## SAFETY DATA SHEET

### 4. FIRST AID MEASURES.

Eye Contact: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.

Skin Contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners. If in doubt, seek medical advice.

Inhalation: Remove to fresh air. If rapid recovery does not occur, obtain medical attention.

Ingestion: If accidentally swallowed, obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 5. FIRE FIGHTING MEASURES.

Extinguishing media: Alcohol resistant foam; CO<sup>2</sup>; powder; water spray/mist.

Do Not Use: Water Jet.

Special Fire Fighting Procedures: Fire exposed containers should be sprayed with water to lessen risk of explosion.

Unusual Fire and Explosion Hazards: Fire will produce dense black smoke containing combustion products which may be a health hazard. Appropriate self-contained breathing apparatus may be required. Run off from fire must not enter drains.

### 6. ACCIDENTAL RELEASE MEASURES.

Procedures for Leaks or Spillages: Extinguish sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours. Refer to protective measures listed in Sections 7 & 8. Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth, and place in a suitable container for disposal with the waste regulations (See Section 13). Do not allow to enter drains or water courses. Clean preferably with a detergent; avoid the use of solvents. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the National Rivers Authority.



Tel: 01827 300500  
Fax: 01827 51333  
Email sales@grafityp.co.uk  
Website: www.grafityp.co.uk

Directors:  
L.J. Gilbert (Managing Director) H. Bosman Jr. (Secretary) R. Coolen (Director)  
J. Bartnicki (Technical Director) N. Stevenson (Sales Director)  
Grafityp UK Limited. Registered Office: Grafitack House, 103 Mariner, Tamworth, Staffordshire, B79 7UL.  
Registration Number: 2191134 England.



## SAFETY DATA SHEET

### 7. HANDLING AND STORAGE.

**Handling:** Vapours are heavier than air any may spread along floors. They may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the Occupation Exposure Limits.

Use only in areas from which all sources of heat, sparks and open flame have been excluded.  
Avoid skin and eye contact.  
Avoid inhalation of vapour and spray mist.  
Smoking, eating and drinking should be prohibited in areas of use and storage.

**Storage:** Store below 50°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking.

Observe the label precautions.

Store separately from strong oxidising agents and strongly alkaline and strongly acidic materials. Containers which are opened should be properly resealed and kept upright to prevent leakage.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION.

INGREDIENT NAME	OSE/MEL	8hr TWA	15 min STEL
Propan-2-ol	OES	400ppm	500ppm (Sk)

**Engineering Measures:** Provide adequate ventilation to maintain the flammable vapour concentration well below the lower explosive limit (LEL) and ensure the airborne concentration of substances to which an OES has been assigned is below that OES (Occupational Exposure Standard).

**Respiratory Protection:** Air-fed respiratory equipment should be worn when this product is sprayed if the exposure of the sprayer or other people nearby cannot be controlled to below the occupational exposure limit and engineering controls and measures cannot reasonably be improved.

**Hand Protection:** When skin exposure may occur, advice may be sought from the glove suppliers on appropriate types. Barrier creams may help to protect exposed areas of skin but are not substitutes for fully physical protection.



Tel: 01827 300500  
Fax: 01827 51333  
Email sales@grafityp.co.uk  
Website: www.grafityp.co.uk

Directors:  
L.J. Gilbert (Managing Director) H. Bosman Jr. (Secretary) R. Coolen (Director)  
J. Bartnicki (Technical Director) N. Stevenson (Sales Director)  
Grafityp UK Limited. Registered Office: Grafitack House, 103 Mariner, Tamworth, Staffordshire, B79 7UL.  
Registration Number: 2191134 England.



## SAFETY DATA SHEET

Eye Protection: Eye protection designed to protect against liquid splashes should be worn.

Skin Protection: Cotton or cotton/synthetic overalls are normally suitable. Grossly Contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner. (SK) denotes product can be absorbed through skin.

### 9. PHYSICAL AND CHEMICAL PROPERTIES.

Physical State:	Liquid
Appearance:	Colourless
Odour/Taste:	Alcoholic
pH:	N/A
Boiling point/boiling range:	82°C
Melting point/melting range:	<0°C
Flash point:	12°C
Flammability: LEL	2.0 (% vol. in air @ 25°C)
Flammability: UEL	12.0
Auto flammability:	>400°C
Explosive properties:	None
Oxidising properties:	None
Relative Density:	0.786
VOC Content:	786 g/L
Water Solubility:	Soluble
Solvent Solubility:	Soluble in alcohols
Other data:	

### 10. STABILITY AND REACTIVITY

Stability: Stable

Conditions to avoid: Avoid naked flames, red hot surfaces, other high temp. sources that may induce thermal decomposition.

Incompatibility (Materials to avoid): Oxidising agents, strong acids, strong alkalis

Hazardous decomposition products: In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produced.



Tel: 01827 300500  
Fax: 01827 51333  
Email sales@grafityp.co.uk  
Website: www.grafityp.co.uk

Directors:  
L.J. Gilbert (Managing Director) H. Bosman Jr. (Secretary) R. Coolen (Director)  
J. Bartnicki (Technical Director) N. Stevenson (Sales Director)  
Grafityp UK Limited. Registered Office: Garfitack House, 103 Mariner, Tamworth, Staffordshire, B79 7UL.  
Registration Number: 2191134 England.



## SAFETY DATA SHEET

### 11. TOXICOLOGICAL INFORMATION.

INGREDIENT LD50 (Animal/oral)

Propan-2-ol 5.8g/Kg (Rat)

Exposure to organic solvent vapours may result in adverse health effects on the renal and central nervous systems. Symptoms can include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Splashes in the eyes may cause irritation and reversible local damage.

Propan-2-ol causes slight to moderate irritation with possible corneal injury in the eyes. The liquid can penetrate the skin and cause dermatitis on prolonged exposure. Low concentrations may cause mild irritation of eyes, nose and throat. Concentrations above the OES may cause headaches, nausea and vomiting. It is slightly toxic by ingestion, causing drowsiness and unconsciousness in extreme cases; 100 ml can be fatal.

### 12. ECOLOGICAL INFORMATION.

The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

Propan-2-ol does not bio-accumulate and is readily biodegradable.

### 13. DISPOSAL CONSIDERATIONS

Do not allow into drains or water courses or dispose of where ground or surface water may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution Act.

Using the information provided in this data sheet, advice should be obtained from the Waste Regulation Authority whether the special waste regulations apply.



Tel: 01827 300500  
Fax: 01827 51333  
Email sales@grafityp.co.uk  
Website: www.grafityp.co.uk

Directors:  
L.J. Gilbert (Managing Director) H. Bosman Jr. (Secretary) R. Coolen (Director)  
J. Bartnicki (Technical Director) N. Stevenson (Sales Director)  
Grafityp UK Limited. Registered Office: Grafitack House, 103 Mariner, Tamworth, Staffordshire, B79 7UL.  
Registration Number: 2191134 England.



## SAFETY DATA SHEET

### 14. TRANSPORT INFORMATION.

CCNN: 3402 90 90  
UN Number: 1219  
IMDG: 3244  
Class: 3.2  
ICAO/IATA:  
RID/ADR:

### 15. REGULATORY INFORMATION.

Label for Supply: HIGHLY FLAMMABLE

Risk Phrases: None

Safety Phrases: 2: Keep out of reach of children.  
7: Keep container tightly closed.  
16: Keep away from source of ignition – No Smoking.  
46: If swallowed seek medical advice immediately and show this container or label.

Regulatory References: The Chemicals (Hazard Information and Packaging) Regulations 1993

### 16. OTHER INFORMATION

The information contained in this data sheet is provided in accordance with the requirements of the Chemicals (Hazard Information and Packaging) Regulations. It does not constitute the user's own assessment of the workplace risks as required by other health and safety legislation. The provisions of the Health & Safety at Work Act and the Control of substances Hazardous to Health Regulations apply to the use of this product at work.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of the relevant legislation are complied with.

OES/MEL values are obtained from the current issue of EH40 unless indicated this (Sup) when a value has been obtained from the supplier.



Tel: 01827 300500  
Fax: 01827 51333  
Email sales@grafityp.co.uk  
Website: www.grafityp.co.uk

Directors:  
L.J. Gilbert (Managing Director) H. Bosman Jr. (Secretary) R. Coolen (Director)  
J. Bartnicki (Technical Director) N. Stevenson (Sales Director)  
Grafityp UK Limited. Registered Office: Grafitack House, 103 Mariner, Tamworth, Staffordshire, B79 7UL.  
Registration Number: 2191134 England.



## SAFETY DATA SHEET

Further information and advice can be found in the following publications:

The Control of Substances Hazardous to Health Regulations 1988 (SI 1988:1657)

The Environmental Protection (Duty of Care) Regulations 1992 (SI 192:2839)

Storage of Packaged Dangerous Substances, HS(G)71

The Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972 (SI1972: 917)

Storage of Flammable Liquids in Containers, HS(G)51

Date of issue of original: 31.05.96

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with legal regulations. The information contained herein is based on the current state of our knowledge and is intended to describe products from the point of view of safety requirements and thus should not be constructed as guaranteeing specific properties. For further information contact the office.



Tel: 01827 300500  
Fax: 01827 51333  
Email [sales@grafityp.co.uk](mailto:sales@grafityp.co.uk)  
Website: [www.grafityp.co.uk](http://www.grafityp.co.uk)

#### Directors:

L.J. Gilbert (Managing Director) H. Bosman Jr. (Secretary) R. Coolen (Director)  
J. Bartnicki (Technical Director) N. Stevenson (Sales Director)  
Grafityp UK Limited. Registered Office: Grafitack House, 103 Mariner, Tamworth, Staffordshire, B79 7UL.  
Registration Number: 2191134 England.

