



DecalExpress LASER DECAL FINISHER

A Dedicated Tool to Satisfy Different Needs for Decal Cutting



CCD Camera (DecalExpress Only)*



Waste Drawer

DecalExpress

DecalExpress-ECO



Paper Loading Cart (Optional)



Waste Removal Roll

Laser Decal Finisher

The DecalExpress is dedicated to satisfy different needs for garment décor market. The powerful SmartCONTROL software makes the operation easier and performs multiplex parameters in one cutting job. The specially designed waste drawer collects unnecessary materials when die cutting, providing a smooth workflow without job interruptions. The DecalExpress with superior and versatile capacities optimizes its performance of decal cutting. To suit with different demand, we release ECO version with budget friendly design. We believe when your business is ready to grow, GCC will be there!



Features:

- Automatic winding / unwinding system
- Beam path with dust protection window to minimize maintenance
- Down vacuum to hold materials flat for laser cutting
- Emergency stop
- CCD Camera to perform precise contour cutting (DecalExpress Only)*
- Waste drawer to collect unnecessary material for cut through function
- Edge guiding module to keep materials consistent feeding
- Top vacuum to take out debris and exhaust during laser cutting
- Reliable steel drum material driven technology
- Built-in LED light to illuminate working space
- Air assist to protect lens of laser carriage
- Automated laser cutting process for fabric cutting with low operating and material costs.

* CCD is standard for regular DecalExpress, optional for DecalExpress-ECO version.

DecalExpress

LASER DECAL FINISHER

| Model Number | | DE24-20V | DE24-30V | DE24-20V(ECO) | DE24-30V(ECO) |
|---------------------------|-------------|--|-------------|--|---------------|
| Wattage | | 20W 9.3-μm | 30W 10.6-μm | 20W 9.3-μm | 30W 10.6-μm |
| Cutting Width | | 610 mm (24") | | | |
| Work Area (Sheet) (W x L) | | 610 x 330 mm (24" x 13") | | | |
| Max. Roll Material Size | Width | 85~610 mm (3.4"~24") | | | |
| | Roll Size | 76.2 mm (3") core with 300 mm (11.8") diameter | | 76.2 mm (3") core with 170 mm (6.7") diameter | |
| | Roll Weight | 25 kgs | | 12 kgs | |
| Laser Source | | Sealed CO2 Laser | | | |
| Drive | | Closed-loop DC Servo Control | | | |
| Roll to Roll | | Stepper motor Control | | | |
| Maximum Motor Speed | | 1,530 mm/s (60ips) (for straight line cutting) | | | |
| Speed Control | | Adjustable from 0.1~100 % (Up to 16 color-linked speed settings per job) | | | |
| Power Control | | Adjustable from 0~100 % (Up to 16 color-linked speed settings per job) | | | |
| Alignment System | | CCD Module | | | |
| Distance Accuracy | | 0.254 mm or 0.1 % of move, whichever is greater | | | |
| Computer Interface | | Standard USB port | | | |
| Operating Systems | | MS Windows | | | |
| Display Panel | | 4-line LCD panel | | | |
| Paper Feeding | | Auto feed sensor, re-winding system, paper alignment control, waste removal system | | | |
| Vacuum System | | Down vacuum for media fixation | | | |
| | | Top vacuum for media surface cleaning | | | |
| Process Materials | | Paper, PET, PP, TNT, BOPP, etc. | | | |
| Safety | | Class IV Laser Product Compliant with EN60825-1:2014 Class IV Laser Product Compliant with CDRH | | | |
| Dimensions (W x L x H) | Machine | 1,135 x 1,441 x 1,180 mm (44.6 x 56.7 x 46.5 in.) | | 1,135 x 700 x 1,305 mm (44.6 x 27.6 x 51.4 in.) | |
| | Shipping | 1,385 x 1,741 x 1,430 mm (54.5 x 68.5 x 56.3 in.) | | 1,230 x 920 x 1,605 mm (48.4 x 36.2 x 63.2 in.) | |
| Weight | Machine | 275 kg | | 90 kg | |
| | Shipping | 375 kg | | 186 kg | |
| Facility Requirements | | | | | |
| Electrical | | 100~240 Volt AC, 50/ 60Hz, Auto Switching, Max. 10 Amp | | | |
| Power Consumption | | MAX:1000W | | | |
| Optional Item | | Air Exhaust System Compressor Slitting device Paper loading cart External I/O board | | | |



*Specifications are subject to change without prior notice.

www.GCCworld.com



| | | | |
|------------------|---|------------------|---------------------------|
| GCC Headquarters | 4F-1., No.236, Fude 2nd Rd., Xizhi Dist., New Taipei City 22151, Taiwan | 886-2-6616-6692 | Fax : 886-2-2694-6875 |
| GCC China | No.1, Chen Feng Road, Yushan, Kunshan, Jiangsu 215300, China | 86-512-5726-1515 | Fax : 86-512-5726-1518 |
| GCC Europe B.V. | Eglantierbaan 43-45, 2908 LV, Capelle a/d IJssel, The Netherlands | 31-10-458-9367 | Fax : 31-10-451-9874 |
| GCC America, Inc | 20453 E Valley Blvd.Walnut, CA 91789, USA | 1-909-718-0248 | Fax : 1-909-718-0251 |
| | | US & Canada Only | Toll Free: 1-888-284-5211 |