

Physical Information

Aluminum

275±10 micron (without liner) / 270±10 g/m² (without liner) / Liner: 50mic PET Film

Strong removable adhesive

Coating & Ink Compatibility

Solvent, Eco solvent, Latex, UV curable ink

Water resistant, Scratch resistant, Slip resistant (ASTM D2047, DIN51130)

Matte – low reflection effect

Advantages

Perfectly absorb Solvent, Latex, UV curable inks with quick dry

Delivers accurate colors and vivid results on its high-quality matte surface

Direct printable - No need additional protective laminate

Dimensional stability

Anti-fouling

Kiss-cutting & Contour cutting

Application

Brick, Tarmac/Asphalt walkway display, Concrete cement, boards sign and any rough or smooth surfaces

Installation

Ensure the surface is completely clean and dry before installing

We do recommend working on a floor with a temperature of 10-30°C. There is no need to heat up floor before application. Initially apply the material by hand (using an applicator roller will help ensure the material conforms to whatever surface it is being applied to) and then tap edges of material with a rubber mallet or use a roller to help with sealing the graphic to the surface.

Storage and Conditions and Shelf Life

To avoid any loss of quality, it should also be stored in suitable conditions, that is at a temperature between 10°C and 20°C, and a relative humidity of 50%

Shelf life – 12month / 6month for outdoor
