

# Product Information

## OWV-LX

### Description

One way vision film design for Latex & UV printers. Create stunning graphics on one side and a clear, unobstructed view from the other. Virtually all glass surfaces now have the potential for maximum visual impact.

### Composition

Media: 160 microns  
Perforations: 1.6mm  
Outdoor Durability: Up to 1 year

### Application

OWV-LX is the perfect window-graphics media for outdoor advertising, including vehicle and building wraps, POP, retail and commercial window signage, public transport, bus shelters, corporate identity and much more.

**Note: Never apply the film against the rubbers or silicones. Make sure you always stay at least 2mm from the edge. Wait at least 24 hours before laminating the printed OWV. When applying on to glass try to avoid touching the glue side with hands.**

### Product Specifications

Item	Data	Unit
Face film	0.16(±0.01)	mm
Face film weight	90	g/m2
Hole diameter	1.6	mm
PVC film shrink rate	< 0.7	%
PVC film colour	Ceramic white vinyl with Black back	
Glue thickness	28	μ
Glue colour	transparent	
Glue type	removable solvent base pressure sensitive glue	
First tack test	170 N/m. ( Test while adhering to stainless steel )	
Final tack test	430 N/m. ( Test while adhering to stainless steel )	
Release paper	Double Liner paper design for UV printer Paper & PET composite	
Release paper weight	120	g/m2
Paper thickness	0.125	mm
Product width	1.37, 1.52	m
Light transmission	40 / 60	
Temperature	-30 ~ +80	°C
UV resistance	excellent	
Expire time	36 months	