

# Product Information

## DSB

### Description

DSB double sided blockout banner print media is suitable for indoor and outdoor use. It is of a smooth, scrim-reinforced construction that is printable on both sides. It features a built-in black layer that prevents images from showing through to the other side.

### Composition

Media: 0.36mm thick  
440g/m<sup>2</sup>

### Application

DSB is ideal for indoor and outdoor use on display banners, roll up display, street banners, and other applications. This product is designed for inkjet printing and screen printing. It is optimised for use on Solvent, Eco-solvent and UV curable inkjet printers.

### Product Specifications

Item	Data		Unit	Method
Yarn	250 x 250		Denier	DIN60001
Net structure	41 x 40		Thread / inch	DIN53853
Net Weight	180		g/m2	DIN53352
PVC Film Weight	260		g/m2	DIN53352
Product Weight	440 (±10)		g/m2	DIN53352
Thickness	0.36 (±0.02)		mm	DIN53353
Product Width	1.02 ~ 3.60		m	-
Tearing Strength	L	170	N/5cm	DIN53353
	W	170		
Tensile Strength	L	520	N/5cm	DIN53354
	W	520		
Elongation Value	L	17	%	DIN53354
	W	17		
Peeling Strength	38		N/5cm	DIN53357
Light Transmission	0		%	ASTM D 1003
Temperature	-30°C ~ +70°C		°C	DIN53372
Expired Time	6 ~ 12 months			-
Flame Retardant	Pass			DIN75200
Anti-wicking	without			
Anti-frost	without			
Anti-mildew	without			
Acrylic lacquer	without			