

Product Information

OWV

Description

OWV One Way Vision film allows for stunning graphics to be printed on one side and a clear, unobstructed view from the other. Virtually all glass surfaces have the potential for maximum visual impact. Up to 1 year lifespan.

Composition

Media: 160 microns
Perforations: 1.5mm

Application

OWV is the perfect window-graphics media for outdoor advertising, including vehicle and building wraps, POP, retail and commercial window signage, public transport, bus shelters, corporate identity and much more.

Note: Never apply the film against the rubbers or silicones. Make sure you always stay at least 2mm from the edge. Wait at least 24 hours before laminating the printed OWV. When applying on to glass try to avoid touching the glue side with hands.

Product Specifications

Item	Data	Unit
Face film	0.15(±0.01)	mm
Face film weight	80	g/m2
Hole diameter	1.5	mm
PVC film shrink rate	< 0.7	%
PVC film colour	black back vinyl	
Glue thickness	20	μ
Glue colour	transparent	
Glue type	removable or permanent	
First tack test	170 N/m. (Test while adhering to stainless steel)	
Final tack test	430 N/m. (Test while adhering to stainless steel)	
Release paper	PE coated paper (PET pad is option)	
Release paper weight	150	g/m2
Paper thickness	0.185	mm
Product width	0.98, 1.27, 1.37, 1.52	m
Light transmission	40 / 60	
Temperature	-30 ~ +80	
UV resistance	excellent	
Expire time	24 ~ 36 months	