

SMESH Print Media

Building and Scaffolding wrap

Description

SMESH is an open weave flexible sign face material. A white print media with regular net structure, soft feel, high tear strength and excellent printability. Suitable for printing on Solvent, Eco-solvent and UV curable printers.

Composition

Media: 75 microns
260 g/m²

Application

SMESH is ideal for printing building and scaffolding wraps, billboard banners, window curtain advertisements and other uses.

Product Specifications

Item	Data		Unit	Method
Yarn	1000 x 1000		Denier	DIN60001
Net structure	12 x 12		Thread / inch	DIN53853
Net Weight	110		g/m ²	DIN53352
PVC Coated	150		g/m ²	DIN53352
Product Weight	260		g/m ²	DIN53352
Thickness	-		mm	DIN53353
Product Width	0.914 ~ 5.00		m	-
Tearing Strength	L	280	N/5cm	DIN53353
	W	280		
Tensile Strength	L	1100	N/5cm	DIN53354
	W	1100		
Elongation Value	L	26	%	DIN53354
	W	26		
Peeling Strength	1017		N/5cm	DIN53357
Light Transmission	-		%	ASTM D 1003
Temperature	-30°C ~ +70°C		°C	DIN53372
Expired Time	6 ~ 12 months			-
Flame Retardant	Pass			DIN75200
Anti-wicking	without			
Anti-frost	without			
Anti-mildew	without			
Acrylic lacquer	without			