

Product Information Mod.R&S 06 | Rev.5 | Update 07/2021 | Page 1

EASY PATTERNS®

SPECIFICATIONS

* Composition	Average Thickness	Carrier	♀ Certifications		
PU	90 microns	non adhesive polyester	REACH n° 1907/2006/EU OEKO-TEX ® CONFIDENCE IN TEXTILES STANDARD 100 20CX00002 CENTROCOT		

۲

Applies on	SUGGESTED CUTTING SETTINGS			TRANSFER SETTINGS			
cotton, polyester, poly/cotton blends (not suited for treated	▲ Blade	≚ Pressure	» Speed	© Time	Temperature	r∠ Pressure	● Peel
and dye sublimated textiles)	45°	50 gf	25 cm/sec	15"seconds	155°C (311°F)	Medium (2,5/3,5 bar)	hot

 \rightarrow Cut the design (not mirrored)

 \rightarrow Weed the excess material

 \rightarrow Remove the print from the carrier with TTD Easy

ightarrow Place the design on the garment

 \rightarrow Heat apply at the conditions shown above

 \rightarrow Remove TTD Easy hot

۲

PRODUCT HIGHLIGHTS

- \rightarrow Easy to cut and weed
- ightarrow Available in variety of patterns

 \rightarrow No printer needed

🗹 NOTE: Given the large number of inks and printers, we highly recommend to perform a test before launching a production

CARE AND WASHING RECOMMENDATIONS

₩ Washing	/ Ironing	🖸 Tumble dry	O Dry cleaning	C Storage Shelf Life	C Storage Temperature	C* Storage Conditions	∮ Position
Up to 40°C, best inside-out	YES best inside-out	YES (delicate setting)	NO	Up to 2 years	Between 18°C and 26°C	Away from sunlight and dust	Vertical

→ Wait 24 hours after the application before the first wash

→ Respect the textile recommendations

→ Do not bleach or use aggressive chemical agents

This document can be subject to variations. Updated versions are available on www.siser.com. For further information, please contact our sales office: info@siser.it



Tel: 01827 300500 sales@grafityp.co.uk Web: www.grafityp.co.uk ۲