

Product Information

Mod.R&S 06 | Rev.4 | Update 02/2020 | Page 1



Glitter 2

Description

Polyurethane heat seal material with high thickness glitters and adhesive polyester backing. It has a rough and brilliant surface. It can be cut with vinyl cutters.

Suitable for cotton, polyester, performance wear, poly/cotton blends and spandex, Not for treated or sublimated textiles.

Usage

- Mirror cut the material
- Weed the exceeding material
- Place the material on the garment with its polyester backing
- Heat apply at the conditions shown on the right
- Remove the carrier warm or cold



Average thickness
350 microns



Suggested cut settings
blade new at 60°
pressure 120 gf
speed 20 cm/sec



Transfer settings
15 seconds at 160°C
(320°F)
medium pressure
(3-4 bar)

Washing

Wait at least 24 hours from application before washing.
Washing resistance up to 40°C, best inside-out.
Do not use bleach or other aggressive chemical agents.
Suitable for dry cleaning.
Not suitable for tumble dryer.

The product is REACH compliant
The product is certified Öko-Tex® Standard 100 Class I
The product is VEGANOK certified

Washing temperature



Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience.
We recommend to perform a test before starting standard production.
For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations. Updated versions are available on our website www.siser.com

For further information, please contact our Sales Office.

GRAFITYP
UK Limited

Tel: 01827 300500
Web: www.grafityp.co.uk
E-mail: sales@grafityp.co.uk