















P.S. ADHESIVE-EASYWEED ADHESIVE

SPECIFICATIONS

			
Composition	Average Thickness	Carrier	Certifications
Copolyester	60 microns	Adhesive polyester	REACH n° 1907/2006/EU  

APPLICATION INSTRUCTIONS









	SUGGESTED CUTTING SETTINGS			TRANSFER SETTINGS			
Applies on							
cotton, polyester, poly/cotton blends (not suited for treated and dye sublimated textiles)	Blade	Pressure	Speed	Time	Temperature	Pressure	Peel
	45°	50 gf	30 cm/sec	5 seconds	150°C (302°F)	Medium (2,5/3,5 bar)	hot

- Remove the pink protective film
- Cut the material mirrored
- Peel off excess material
- Transfer following the recommended parameters
- Remove the carrier while hot

- **PRODUCT HIGHLIGHTS**
- Lightweight material, suitable for the application of screen printing foils

 **NOTE:** We highly recommend to perform a test before launching a production

CARE AND WASHING RECOMMENDATIONS

							
Washing	Ironing	Tumble dry	Dry cleaning	Storage Shelf Life	Storage Temperature	Storage Conditions	Position
Up to 40°C, best inside-out	YES best inside-out	NO	NO	Up to 2 years	Between 18°C and 26°C	Away from sunlight and dust	Vertical

- Wait 24 hours after the application before the first wash
- Respect the textile recommendations
- Do not bleach or use aggressive chemical agents