

P.S.FILM - EASYWEED

SPECIFICATIONS

Composition	्रं Avarage Thickness	Carrier	Certifications			
PU	90 microns	Adhesive polyester	REACH n° 1907/2006/EU OEKO-TEX®			
			STANDARD 100 084270.0 CENTROCOT			

APPLICATION INSTRUCTIONS

⊘ Applies on	SUGGESTED CUTTING SETTINGS			TRANSFER SETTINGS			
cotton, polyester, poly/ cotton blends (not suited for treated and dye sublimated textiles)	Blade	<u></u> Pressure	>> Speed	Time	Temperature	Pressure	Peel
	45°	60 gf	30 cm/sec	15 seconds	150°C (302°F)	Medium (2,5/3,5 bar)	hot/cold

- → Cut the material mirrored
- → Peel off excess material (Tip: use a heated surface for faster and easier "weeding")
- ightarrow Place the decoration on the garment
- → Apply following the recommended parameters
- → Remove the carrier hot or cold

PRODUCT HIGHLIGHTS

- \rightarrow Wide range of colors
- → Can be Layered
- → Suitable for clothing for children and babies
- $oldsymbol{oldsymbol{\mathcal{L}}}$ NOTE: We highly recommend to perform a test before launching a production.

CARE AND WASHING RECOMMENDATIONS

Washing	Ironing	Tumble dry	Ony cleaning	Storage Shelf Life	Storage Temperature	Storage Conditions	∮ Position
Up to 80°C, inside-out	YES inside-out	YES (synthetic cycle)	YES	Up to 2 years	Between 18°C and 26°C	Away from sunlight and dust	Vertical

- → Wait 24 hours after the application before the first wash
- ightarrow Respect the textile recommendations
- → Do not bleach or use aggressive chemical agents



Tel: 01827 300500 Web: www.grafityp.co.uk E-mail: sales@grafityp.co.uk