

P.S. SOFT

SPECIFICATIONS

Composition	स्टें Average Thickness	Q Carrier	♣ Certifications			
PU	85 microns	Adhesive polyester	REACH n° 1907/2006/EU			
			OEKO-TEX ® CONFIDENCE IN TEXTILES STANDARD 100 15.HIT.75858 HOHENSTEIN HTTI			

APPLICATION INSTRUCTIONS

⊘ Applies on	SUGGESTED CUTTING SETTINGS			TRANSFER SETTINGS			
cotton, polyester, poly/ cotton blends,elastan (not suited for treated	Blade	<u></u> Pressure	>> Speed	Time	Temperature	Pressure	Peel
and dye sublimated textiles)	45°	70 gf	20 cm/sec	15 seconds	155°C (311°F)	Medium (2,5/3,5 bar)	hot

- → Cut the material mirrored
- → Peel off excess material
- \rightarrow Place the decoration on the garment
- → Apply following the recommended parameters
- → Remove the carrier while hot

PRODUCT HIGHLIGHTS

- → Extremely thin
- → Very soft touch
- → High elasticity
- NOTE: We highly recommend to perform a test before launching a production

CARE AND WASHING RECOMMANDATIONS

Washing	Ironing	Tumble dry	Ony cleaning	Storage Shelf Life	Storage Temperature	Storage Conditions	∮ Position
Up to 60°C, best inside-out	YES best inside-out	YES (synthetic cycle)	NO	Up to 2 years	Between 18°C and 26°C	Away from sunlight and dust	Vertical

- → Wait 24 hours after the application before the first wash
- → Respect the textile recommendations
- → Do not bleach or use aggressive chemical agents



Tel: 01827 300500 Web: www.grafityp.co.uk E-mail: sales@grafityp.co.uk