



Product Information

Mod.R&S 06 | Rev.4 | Update 08/2019 | Page 1





Whiteboard


Description PU plotter cut heat seal material with adhesive polyester backing. Blackboard surface has been especially created for chalk writing. It can be easily washed and rewritten infinite times. The material grants easy cutting, weeding and application.

Suitable for cotton, polyester, performance wear, poly/cotton blends and spandex, not treated.

- Usage**
- Mirror cut the material
 - Weed the exceeding material
 - Place the material on the garment with its polyester backing
 - Heat apply at the conditions shown on the right
 - Remove the carrier warm

 **Average thickness**
160 microns

 **Suggested cutting settings**
Blade: 45°
Pressure: 90 gf
Speed: 20 cm/sec

 **Transfer settings**
15 seconds at 135°C
(275°F)
medium pressure
(3-4 bar)

Washing Wait at least **24 hours** from application before washing. Washing resistance up to **40°C**, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Suitable for tumble dryer, synthetic cycle.

The product is REACH compliant
The product is VEGANOK certified



Washing temperature



Dry cleaning



Tumble dryer



N.B. We recommend to perform a test before starting standard production.
All information here contained are based on our experience.
For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations. Updated versions are available on our website www.siser.com

GRAFITYP
UK Limited

Tel: 01827 300500
Web: www.grafityp.co.uk
E-mail: sales@grafityp.co.uk