

GLITTER

SPECIFICATIONS

Composition	्रं Average Thickness	Carrier	Certifications			
			REACH n° 1907/2006/EU			
PU	350 microns	Adhesive polyester	OEKO-TEX ® CONFIDENCE IN TEXTILES STANDARD 100 17(Y)0039 CENTROCOT			

APPLICATION INSTRUCTIONS

	SUGGESTED CUTTING SETTINGS			TRANSFER SETTINGS			
cotton, polyester, poly/cotton blends (not suited for treated and dye sublimated textiles)	Blade	≝ Pressure	>> Speed	Time	Temperature	Pressure	Peel
	60°	120 gf	20 cm/sec	15 seconds	160°C (320°F)	Medium (2,5/3,5 bar)	hot/cold

- → Mirror cut the design
- → Weed excess material
- > Place the design on the garment
- → Heat apply at the conditions shown above
- → Peel carrier hot/cold

PRODUCT HIGHLIGHTS

- → over 50 colors available
- ightarrow perfect for trendy or fashion items
- → "WOW" effect
- $oldsymbol{\mathcal{L}}$ NOTE: We highly recommend to perform a test before launching a production.

CARE AND WASHING RECOMMENDATIONS

W Washing	Ironing	Tumble dry	Ony cleaning	Storage Shelf Life	Storage Temperature	Storage Conditions	∮ ⊳ Position
Up to 40°C, inside-out	YES inside-out	NO	YES	Up to 2 years	Between 18°C and 26°C	Away from sunlight and dust	Vertical

- → Wait 24 hours after the application before the first wash
- → Respect the textile recommendations
- → Do not bleach or use aggressive chemical agents



Tel: 01827 300500 Web: www.grafityp.co.uk E-mail: sales@grafityp.co.uk