

# P.S. EASYWEED INK BLOCK LT

## **SPECIFICATIONS**

| Composition | Average Thickness | Carrier            | <b>↑</b> Certifications   |  |  |  |
|-------------|-------------------|--------------------|---|--|--|--|
| PU          | 110 microns       | Adhesive polyester | REACH n° 1907/2006/EU  OEKO-TEX ®  CONFIDENCE IN TEXTILES  STANDARD 100  14000001 CENTROCOT  * except fluo-colors |  |  |  |

# APPLICATION INSTRUCTIONS

| ⊘<br>Applies on       | SUGGESTED CUTTING SETTINGS |                  |           | TRANSFER SETTINGS |                  |                          |          |
|-----------------------|----------------------------|------------------|-----------|-------------------|------------------|--------------------------|----------|
| textiles colored with | Blade                      | <u></u> Pressure | >> Speed  | Time              | Temperature      | Pressure                 | Peel     |
| sublimation inks      | 45°                        | 60 gf            | 30 cm/sec | 15 seconds        | 135°C<br>(275°F) | Medium<br>( 2,5/3,5 bar) | hot/cold |

- → Cut the material mirrored
- $\rightarrow$  Peel off excess material
- → Place the decoration on the garment
- → Apply following the recommended parameters
- → Remove the carrier hot or cold

#### **PRODUCT HIGHLIGHTS**

- ightarrow Low temperature transfer
- → Specific for sublimation dyed fabrics
- → Stops ink migration on sublimation polyester fabrics

NOTE: We highly recommend to perform a test before launching a production

## CARE AND WASHING RECOMMENDATIONS

| Washing                            | Ironing | <b>⊡</b> Tumble dry | Dry cleaning | Storage<br>Shelf Life | Storage<br>Temperature   | Storage<br>Conditions             | <b>∮</b><br>Position |
|------------------------------------|---------|---------------------|--------------|-----------------------|--------------------------|-----------------------------------|----------------------|
| Up to 40°C,<br>best inside-<br>out | NO      | NO                  | NO           | Up to 2 years         | Between 18°C<br>and 26°C | Away from<br>sunlight and<br>dust | Vertical             |

- → Wait 24 hours after the application before the first wash
- ightarrow Respect the textile recommendations
- → Do not bleach or use aggressive chemical agents



Tel: 01827 300500 Web: www.grafityp.co.uk E-mail: sales@grafityp.co.uk