

C-PRINT INK BLOCK PU LT

SPECIFICATIONS

Composition	Average Thickness	Carrier	Certifications
PU	110 microns	Non adhesive polyester	<p>REACH n° 1907/2006/EU</p> <p>OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100 14CX00052 CENTROCOT</p> <p>VEGANOK AZIENDA N. 1004</p> <p>VEGAN</p>

APPLICATION INSTRUCTIONS

Applies on	SUGGESTED CUTTING SETTINGS			TRANSFER SETTINGS			
textiles colored with sublimation inks	Blade	Pressure	Speed	Time	Temperature	Pressure	Peel
	45°	80 gf	20 cm/sec	15 seconds	135°C (275°F)	Medium (2,5 bar)	hot

- Print, Cut and peel off excess material
- Remove the print from the support with the help of TTD Easy
- Place the decoration on the fabric
- Apply following the recommended parameters
- Remove the TTD while hot

PRODUCT HIGHLIGHTS

- Anti migration barrier
- Suitable for sublimation dyed fabrics
- Low temperature transfer

NOTE: Given the large number of sublimation inks and printers, we highly recommend to perform a test before launching a production

CARE AND WASHING RECOMMENDATIONS

Washing	Ironing	Tumble dry	Dry cleaning	Storage Shelf Life	Storage Temperature	Storage Conditions	Position
Up to 40°C, best inside-out	NO	NO	NO	Up to 2 years	Between 18°C and 26°C	Away from sunlight and dust	Vertical

- Wait 24 hours after the application before the first wash
- Respect the textile recommendations
- Do not bleach or use aggressive chemical agents