



C-PRINT®

SPECIFICATIONS

Composition	Average Thickness	Carrier	Certifications
PVC	170 microns	non adhesive polyester	<p>REACH n° 1907/2006/EU</p> <p>   </p> <p>Certified for HP Latex Inks</p>

APPLICATION INSTRUCTIONS

APPLIES ON	SUGGESTED CUTTING SETTINGS			TRANSFER SETTINGS			
cotton, polyester, performance wear, poly/cotton blends and spandex, not treated or dye sublimated	Blade	Pressure	Speed	Time	Temperature	Pressure	Peel
	45°	70 gf	20cm/sec	15 seconds	150°C (302°F)	Medium (2,5/3,5 bar)	hot

- Print, cut and peel off excess material
- Remove the print from the carrier with the help of TTD Easy
- Place the decoration on the fabric
- Apply following the recommended parameters
- Remove the TTD while hot

PRODUCT HIGHLIGHTS

- Bright colours
- High resistance to washing
- Can be printed with HP Latex inks

 **NOTE:** Given the large number of inks and printers, we highly recommend to perform a test before launching a production

CARE AND WASHING RECOMMENDATIONS

Washing	Ironing	Tumble dry	Dry cleaning	Storage Shelf Life	Storage Temperature	Storage Conditions	Position
Up to 60°C, best inside-out	YES best inside-out	NO	NO	Up to 2 years	Between 18°C and 26°C	Away from sunlight and dust	Vertical

- Wait 24 hours after the application before the first wash
- Respect the textile recommendations
- Do not bleach or use aggressive chemical agents