

SOFT PRINT COLOUR

SPECIFICATIONS

Composition	Average Thickness	© Carrier				
	45 microns	Non adhesive polyester	REACH n° 1907/2006/EU			
PU			OEKO-TEX ® CONFIDENCE IN TEXTILES STANDARD 100 1400240.0 CENTROCOT			

APPLICATION INSTRUCTIONS

⊘ Applies on	SUGGESTED CUTTING SETTINGS			TRANSFER SETTINGS			
cotton, polyester, poly/ cotton blends, elastan (not suited for treated	Blade	<u></u> Pressure	>> Speed	Time	Temperature	Pressure	Peel
and dye sublimated textiles)	45°	60 gf	30 cm/sec	15 seconds	155°C (311°F)	Medium (2,5/3,5 bar)	hot

- → Print, Cut and peel off excess material
- → Remove the print from the support with the help of the TTD
- → Place the decoration on the fabric
- → Apply following the recommended parameters
- → Remove the TTD while hot
 - PRODUCT HIGHLIGHTS
- → Very Thin
- → For Colored Garments
- → Elastic material

NOTE: Given the large number of inks and printers, we highly recommend to perform a test before launching a production

CARE AND WASHING RECOMMENDATIONS

Washing	Ironing	Tumble dry	Ony cleaning	Storage Shelf Life	Storage Temperature	Storage Conditions	∮ Position
Up to 40°C, best inside-out	YES best inside-out	NO	NO	Up to 2 years	Between 18°C and 26°C	Away from sunlight and dust	Vertical

- → Wait 24 hours after the application before the first wash
- ightarrow Respect the textile recommendations
- → Do not bleach or use aggressive chemical agents



Tel: 01827 300500 Web: www.grafityp.co.uk E-mail: sales@grafityp.co.uk