














COLORPRINT® PU EXTRA MATT / GLOSSY SP

SPECIFICATIONS

 Composition	 Average Thickness	 Carrier	 Certifications
PU	70 microns	non adhesive polyester	REACH n° 1907/2006/EU 

APPLICATION INSTRUCTIONS

 APPLIES ON	SUGGESTED CUTTING SETTINGS			TRANSFER SETTINGS			
nylon, polyester, treated fabrics,	 Blade	 Pressure	 Speed	 Time	 Temperature	 Pressure	 Peel
	45°	75 gf	25 cm/sec	15 seconds	155°C (311°F)	Medium (2,5/3,5 bar)	hot









- Print, cut and peel off excess material
- Remove the print from the carrier with the help of TTD Easy
- Place the decoration on the fabric
- Apply following the recommended parameters
- Remove the TTD while hot

PRODUCT HIGHLIGHTS

- Available in glossy or matte version
- Very Thin Product
- Applicable on difficult fabrics (nylon, leather, tnt)

 **NOTE:** Given the large number of inks and printers, we highly recommend to perform a test before launching a production

CARE AND WASHING RECOMMENDATIONS

 Washing	 Ironing	 Tumble dry	 Dry cleaning	 Storage Shelf Life	 Storage Temperature	 Storage Conditions	 Position
Up to 40°C, best inside-out	NO	YES (synthetic cycle)	NO	Up to 2 years	Between 18°C and 26°C	Away from sunlight and dust	Vertical

- Wait 24 hours after the application before the first wash
- Respect the textile recommendations
- Do not bleach or use aggressive chemical agents