







Grafiflex Videoflex Extra

Apply to nylon and other difficult fabrics

Description

Videoflex Extra is a tough thermoweldable computer cut material for application on any type of “tough” textiles. For use on nylons (nylon jackets, K-Way, nylon sports wear and bags), umbrellas, leather etc.

Suitable for application to:

Cotton	Poly/cotton	Polyester	Lycra®	Nylon	Leather	Treated Fabrics	Not suited for dye sublimation fabrics. If applied to treated fabrics we suggest a prior application and washing test
							

Cutting & Pressing Information:

Vinyl Cutter/Plotter Settings: Blade: new at 45°

Minimum required pressure: 50gf

- 1 Remove protective liner first
- 2 Cut in REVERSE
- 3 Heat apply for 2 - 4 second with its own polyester backing
- 4 Remove backing when cold
- 5 Cover with silicon treated paper or teflon
- 6 Heat apply for a further 10 seconds

Due to the many different base materials available on the market, these heat transfer instructions are given as a guideline only.



Certifications: This product is REACH compliant and certified Öeko-Tex® Standard 100 Class I

Washing & Care guidelines:



Wait 24 hours after heat transfer before washing. Do not use bleach or other aggressive chemical agents. Do not dry clean. Can be tumble dried.