



# Product Information

Mod.R&S 06 | Rev.4 | Update 10/2017 | Page 1



## PS Electric (EasyWeed Electric)

**Description** PU plotter cut heat seal material with adhesive polyester backing and bright colors.

The material grants a good workability during the weeding and application phases and is highly wash-resistant. Recommended for overlaying applications.

Suitable for white or light coloured textiles in cotton, polyester, blends of these materials, not treated or dye sublimated.

### Usage

- Mirror cut the material
- Weed the exceeding material
- Place the material on the garment with its polyester backing
- Heat apply at the conditions shown on the right
- Remove the support warm



**Average thickness**

90 microns



**Suggested cutting settings**

blade new at 45°  
pressure 60 gf  
speed 30 cm/sec



**Transfer settings**

15 seconds at 150°C  
(300°F)  
medium pressure  
(3-4 bar)

### Washing

Wait at least **24 hours** from application before washing.

Washing resistance up to **60°C**, best inside-out.

Do not use bleach or other aggressive chemical agents.

Not suitable for dry cleaning

Suitable for tumble dry, cotton cycle

Washing temperature



Dry cleaning



Tumble dryer



The product is REACH compliant

The product is certified Öko-Tex® Standard 100 Class I



**N.B.** All information here contained are based on our experience.  
We recommend to perform a test before starting standard production.  
For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C



Management System  
ISO 9001:2015



www.tuv.com  
ID 9105027958

The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations.

Updated versions are available on our website [www.siser.com](http://www.siser.com)

For further information, please contact our Sales Office.

Thank you

Tel: 01827 300500  
Web: [www.grafityp.co.uk](http://www.grafityp.co.uk)  
E-mail: [sales@grafityp.co.uk](mailto:sales@grafityp.co.uk)