PS Metallic

Description

Plotter cut heat seal material with adhesive polyester backing and a gold or silver metallic finish.
Due to the unique nature of its metallic surface, it can be used for **medium to large cuttings** and **single layer** applications only.
Avoid bending the application once transferred.

Suitable for cotton, polyester or poly/cotton blends, not treated or dye sublimated

Average thickness
100 microns

Suggested cutting settings
Blade: 60°
Pressure: 130 gf
Speed: 15 cm/sec

Usage

- Mirror cut the material
- Weed the exceeding material
- Place the material on the garment with its polyester backing
- Heat apply at the conditions shown on the right
- Remove the carrier warm or cold

Transfer settings
15 seconds at 160°C (320°F)
medium pressure (3-4 bar)

Washing

Wait at least **24 hours** from application before washing.
Hand washing recommended, best if inside-out.
Do not use bleach or other aggressive chemical agents.
Not suitable for dry cleaning.
Not suitable for tumble dryer.

The product is REACH compliant

Washing temperature

Dry cleaning

Tumble dryer

N.B. All information here contained are based on our experience.
We recommend to perform a test before starting standard production.
For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C

TÜVRheinland CERTIFIED
Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9105027958

The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).
This document can be subject to variations. Updated versions are available on our website www.siser.com
For further information, please contact our Sales Office.

GRAFITYP
Tel: 01827 300500
Web: www.grafityp.co.uk
E-mail: sales@grafityp.co.uk