

INK-JET BASIC WT

FOR COTTON

1-PAPER-SYSTEM



PRINT SETTINGS

- Image Mode: mirrored
- Only for use in Ink-Jet printers and with dye-based or pigment inks!



TRANSFER PROCESS

- Place the textile on the lower plate of the transfer press.
- Pre-Press the t-shirt for a few seconds.
- Place the transfer paper onto the t-shirt.
- Press as mentioned below.
- Peel off the transfer paper after cooling down completely.



SETTINGS HEAT PRESS

	AUTOMATIC HEAT PRESS	MANUAL HEAT PRESS
PRESSURE	3 bar / 43 PSI	medium
TEMPERATURE	175°C / 347°F	175°C / 347°F
TIME	20 seconds	20 seconds



WASHING

• Up to 30°C (cold wash cycle). Inside out. Do not use fabric softener or liquid detergent.



DRYING

• Do not tumble dry! Hang dry or line dry recommended



IRONING

• When ironing cover the print with baking paper

Before starting a mass production, we recommend to make transfer and washing test with all materials. Important advice for double-sided printing on textiles: T-Shirts for a double-sided print (front side & backside), has to be put over the lower heat plate. In this case only one side will be treated with heat and you avoid that the applied design from the other side will be pressed out again. If your T-Shirt is yellowing, lay a piece of fleece onto it during the transfer process.

Tel: 01827 300500 E-mail: sales@grafityp.co.uk Web: www.grafityp.co.uk